Odor Petroleum distillates

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name NP-1 AEROSOL Recommended use Lubricant Information on Manufacturer CHEMSEARCH DIV. OF NCH CORP. BOX 152170

Product Code 5607 Chemical nature Petroleum distillates mixture **Emergency Telephone Number** CHEMTREC® 800-424-9300

### 2. HAZARDS IDENTIFICATION

**Emergency Overview** DANGER Extremely flammable May be harmful if inhaled Causes skin irritation Causes eye irritation Harmful or fatal if swallowed Contents under pressure

Color Off-white

**IRVING, TX 75015** 

Potential Health Effects Principle Route of Exposure Primary Routes of Entry

**Acute Effects** 

Eyes

Skin Inhalation

Ingestion **Chronic Toxicity** 

**Target Organ Effects** 

Aggravated Medical Conditions Potential Environmental Effects Physical State Liquid

Skin contact, Eye contact, Inhalation. Inhalation, Skin Absorption.

Causes eye irritation.

Causes skin irritation. May be absorbed through the skin in harmful amounts.

May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Repeated and prolonged exposure to solvents may cause brain and nervous system damage. Prolonged or repeated inhalation may cause damage to the lungs. Prolonged skin contact may defat the skin and produce dermatitis. Suspect reproductive hazard - contains material which may injure unborn child. Kidney injury may occur.

Respiratory system, Central nervous system, Peripheral Nervous System (PNS), Ears, Skin, Eyes, Kidney, Heart.

Respiratory disorders, Skin disorders, Neurological disorders, Kidney disorders, Heart disease.

See Section 12 for additional Ecological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No CAS-No
Methyl acetate	79-20-9
Hexane	110-54-3
Propane	74-98-6
Petrolatum	8009-03-8
Butane Butane	106-97-8
3-methylpentane	96-14-0
Methylcyclopentane	96-37-7
2-Methylpentane	107-83-5

# 4. FIRST AID MEASURES

General advice **Eye Contact** 

**Skin Contact** 

Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops

Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-

Inhalation Ingestion If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person. Rinse mouth.

Notes to physician

Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Flash Point

75 °F / 24 °C

Method

Seta closed cup

Autoignition Temperature No information available.

Flammability Limits in Air % Solvent mixture.

Upper 16

Lower 1.05

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Extremely flammable. Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >18 inches / >46 cm and Burnback: 2 inch / 5 cm. Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure -demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) -

**NFPA** 

Health 2

Flammability 4

Instability 0

HMIS

Health 2

Flammability 4

Instability 0

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

**Environmental Precautions Methods for Containment** 

Do not flush into surface water or sanitary sewer system.

Contain spillage, soak up with non -combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

section 13)

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

**Neutralizing Agent** 

Not applicable.

### 7. HANDLING AND STORAGE

Handling

Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors, mist or

gas. Avoid contact with skin, eyes and clothing.

Storage

Keep away from heat and sources of ignition. Store in original container. Keep in a dry, cool and well -

ventilated place.

Storage Temperature

Minimum

Indoor

35 °F / 2 °C

Maximum

120 °F / 49 °C

Storage Conditions

X Outdoor Heated

Refrigerated

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines** 

Component	ACGIH TLV	OSHA PEL	NIOSH
Methyl acetate	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>	IDLH: 3100 ppm STEL 250 ppm STEL 760 mg/m <sup>3</sup>
			TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>
Hexane	TWA: 50 ppm Skin	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup>	IDLH: 1100 ppm TWA: 50 ppm
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	TWA: 180 mg/m <sup>3</sup> IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Petrolatum	5 mg/m <sup>3</sup> as oil mist	10 mg/m <sup>3</sup> as oil mist	No data available
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
3-methylpentane	No data available	No data available	No data available
Methylcyclopentane	No data available	No data available	No data available
2-Methylpentane	No data available	No data available	No data available

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

**Personal Protective Equipment** 

Eye/Face Protection **Skin Protection** 

Respiratory Protection

Safety glasses with side-shields.

Wear suitable protective clothing, Impervious gloves.

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations

# **General Hygiene Considerations**

above the exposure limit they must use appropriate certified respirators.

Viscosity

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

 Physical State
 Liquid

 Color
 Off-white

 Appearance
 Cloudy

 Specific Gravity
 0.731

 Percent Volatile (Volume)
 90.6

 VOC Content (g/L)
 355

 Vapor Density
 1.7 (Air = 1.0)

Odor pH Evaporation Rate VOC Content (%) Vapor Pressure Non viscous
Petroleum distillates
Not applicable
53.25 (Butyl acetate=1)
48.5
1891 mmHg @ 70°F

**Solubility** Negligible

### **10. STABILITY AND REACTIVITY**

Chemical Stability Conditions to Avoid Incompatible Products

Boiling Point/Range

Hazardous Decomposition Products Possibility of Hazardous Reactions Stable. Hazardous polymerization does not occur.

Heat, flames, and sparks

Strong oxidizing agents, Reducing agents, Strong acids, Strong bases,

Molten alkali metals.

Carbon oxides, Hydrogen fluoride. None under normal processing

# 11. TOXICOLOGICAL INFORMATION

### **Product Information**

No information available

134 °F / 57 °C

## **Component Information**

**Acute Toxicity** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Methyl acetate	> 5000 mg/kg ( Rat )	> 5 g/kg (Rabbit)	= 16000 ppm (Rat) 4 h	no data available	no data available
Hexane	no data available	= 3000 mg/kg ( Rabbit )	= 48000 ppm (Rat) 4 h	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Petrolatum	no data available	= 3600 mg/kg ( Rabbit )	no data available	no data available	no data available
Butane	no data available	no data available	= 658 g/m <sup>3</sup> (Rat) 4 h	no data available	no data available
3-methylpentane	no data available	no data available	no data available	no data available	no data available
Methylcyclopentane	no data available	no data available	no data available	no data available	no data available
2-Methylpentane	no data available	no data available	no data available	no data available	no data available

**Chronic Toxicity** 

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Methyl acetate	no data available	no data available	no data available	no data available	eyes, CNS, respiratory system, skin
Hexane	no data available	no data available	no data available	yes	eyes, CNS, respiratory system, auditory system, skin, PNS, heart
Propane	no data available	no data available	no data available	no data available	CNS, heart
Petrolatum	no data available	no data available	no data available	no data available	no data available
Butane	no data available	no data available	no data available	no data available	CNS, heart
3-methylpentane	no data available	no data available	no data available	no data available	no data available
Methylcyclopentane	no data available	no data available	no data available	no data available	no data available
2-Methylpentane	no data available	no data available	no data available	no data available	no data available

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
Methyl acetate	not applicable				
Hexane	not applicable				
Propane	not applicable				
Petrolatum	not applicable				
Butane	not applicable				
3-methylpentane	not applicable				
Methylcyclopentane	not applicable				
2-Methylpentane	not applicable				

## **Product Information**

No information available.

**Component Information** 

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Methyl acetate	EC50 > 120 mg/L Desmodesmus subspicatus 72 h	LC50 295 - 348 mg/L Pimephales promelas 96 h LC50 250 - 350 mg/L Brachydanio rerio 96 h	EC50 = 6000 mg/L 16 h EC50 = 6100 mg/L 30 min	EC50= 1026.7 mg/L 48 h	0.18
Hexane	no data available	LC50 2.1 - 2.98 mg/L Pimephales promelas 96 h	no data available	EC50> 1000 mg/L 24 h	N/A
Propane	no data available	no data available	no data available	no data available	2.3
Petrolatum	no data available	no data available	no data available	no data available	N/A
Butane	no data available	no data available	no data available	no data available	2.89
3-methylpentane	no data available	no data available	no data available	no data available	N/A
Methylcyclopentane	no data available	no data available	no data available	no data available	N/A
2-Methylpentane	no data available	no data available	no data available	no data available	N/A

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

## 13. DISPOSAL CONSIDERATIONS

**Product Disposal** 

Dispose of in accordance with local regulations.

**Container Disposal** 

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be

taken for local recycling, recovery, or waste disposal.

### 14. TRANSPORT INFORMATION

DOT

**Proper Shipping Name** 

**Consumer Commodity** 

**Hazard Class** 

ORM-D

Description

Consumer Commodity, ORM-D

TDG

Proper shipping name

Consumer Commodity

**Hazard Class** 

ORM-D

Description Consumer Commodity, ORM-D

**ICAO** 

UN-No

UN1950

**Proper Shipping Name** 

Aerosols

**Hazard Class** 

**Shipping Description** 

UN1950, AEROSOLS, 2.1, LTD QTY

IATA

UN-No

UN1950

**Proper Shipping Name** 

Aerosols, flammable

**Hazard Class** 

2.1

**ERG Code** 

10L

**Shipping Description** 

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

IMDG/IMO

**Proper Shipping Name** 

Aerosols

**Hazard Class** 

UN-No

UN1950

EmS No. **Shipping Description**  F-D, S-U

## 15. REGULATORY INFORMATION

UN1950, AEROSOLS, FLAMMABLE, 2.1, (15°C c.c.), LTD QTY

Inventories

**TSCA** DSL

Complies Complies

U.S. Federal Regulations

**SARA 313** 

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component SARA 313 - Threshold CAS-No Weight %

			Values
Hexane	110-54-3	5-10	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl acetate	Not applicable	Not applicable
Hexane	5000 lb	Not applicable
Propane	Not applicable	Not applicable
Petrolatum	Not applicable	Not applicable
Butane	Not applicable	Not applicable
3-methylpentane	Not applicable	Not applicable
Methylcyclopentane	Not applicable	Not applicable
2-Methylpentane	Not applicable	Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### **WHMIS Hazard Class**

A Compressed gases B5 Flammable aerosol D2A Very toxic materials D2B Toxic materials



## **16. OTHER INFORMATION**

Prepared By Devon Kebodeaux Supercedes Date 12/28/2010 Issuing Date 10/08/2013

Reason for Revision
Glossary
No information available.
List of References.
No information available.

CHEMSEARCH DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.