

MANUFACTURER'S NAME
BENJAMIN MOORE & CO.
51 CHESTNUT RIDGE RD.
MONTVALE, NJ 07645

EMERGENCY TELEPHONE NO.
800-424-9300

EMERGENCY TELEPHONE NO. 800-424-9300

DATE OF PREPARATION
25-JUN-90

INFORMATION TELEPHONE NO.
201-573-9600

SECTION I - PRODUCT ID

PRODUCT CODE: 220

CLASS: WATER THINNED PAINT

NAME: I/C RETARDO LATEX FIRE RETARDANT
PAINT

COLOR: ALL

HMIS CODE

Health: 1
Flammability: 0
Reactivity: 0
Personal Prot.: B

SARA TITLE 312

Acute: NO
Chronic: NO
Fire: NO
Pressure: NO
React: NO

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	MAX PCT	CAS NO.	TLV	PEL	STEL	CEIL	MM Hg	TEMP
Melamine (f3n)	7.4	108781	N/E	N/E	N/E	N/E		N/A
Pentaerythritol (f*)	6.9	115775	10mg/m3	10mg/m3				N/A
Titanium Dioxide (f*n)	5.4	13463677	10mg/m3	10mg/m3				N/A

f Federal Hazard List

* Hazardous only as dust when product is sanded.

3 Sect. 313 of the Emergency Planning & Community Right-To-Know Act of 1986 and of 40 CFR 372
n New Jersey Label Law hazardous chemical

SECTION III - PHYSICAL DATA

BOILING RANGE: N/A VAPOR DENSITY: HEAVIER THAN AIR WEIGHT PER GAL: 10.8 - 10.8
EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 51.8 - 51.8

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: NOT REGULATED

FLASH POINT: >250°F PMCC

LEL: Not Applicable

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers may burst if exposed to extreme heat or fire.
Toxic gases may form when product burns.

SPECIAL FIREFIGHTING PROCEDURES:

Cool exposed containers with water. Use self-contained breathing apparatus.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - ACUTE:

Inhalation - Irritation of the respiratory tract.

Skin and Eye Contact - Primary irritation.

Ingestion of large amounts could cause serious injury.

EFFECTS OF OVEREXPOSURE - CHRONIC:

None Known

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation - Remove to fresh air. Get medical help for any breathing difficulty.

Eye Contact - Flush thoroughly with water. Call physician.

Skin Contact - Wash with soap and water.

Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Call physician.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS:

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust.

Close container after each use. Keep out of reach of children. Do not take internally.