

MATERIAL SAFETY DATA SHEET :MSDS CODE:RCOMP
Date of Preparation :04/13/93
Manufacturer's Name :FLEX PROOF INCORPORATED
Address :2106 24th Avenue South
City, State, Zip :Seattle, WA 98144-4632 U.S.A.
Emergency Telephone Number :1-800-255-3924 CHEM-TEL, INC.
Manufacturer Telephone Number :1-206-328-5540 FLEX PROOF INC.

HMIS HAZARD RATING KEY
4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant
(See Section 1)

Section 1 Product Identification

Product :R Compound
Common Name :Grain Mold Compound
Chemical Family :Silicone fluid with filler and curing agents
Formula :mixture
Hazard Rating (Key above): Health: 0 Flammability: 0 Reactivity: 0 Special Hazards: none

Section 2 Hazardous Ingredients

Chemical/Common Name	CAS Number	%	ACGIH-TLV	OSHA/PEL	OTHER
----------------------	------------	---	-----------	----------	-------

Silicone Rubber			not considered hazardous		
-----------------	--	--	--------------------------	--	--

Section 3 Chemical Data

Boiling Range High: Low: not applicable
Vapor Pressure (mmHg) :not applicable
Vapor Density (Air=1) :not applicable
Evaporation Rate(nBuAcetate=1):not applicable
Specific Gravity : 1.4
Percent Volatile by Weight :nil
Solubility :negligible solubility in water
Appearance/Odor :white viscous liquid with characteristic odor

Section 4 Health Hazard Data

Acute Health Effects :non-irritant to rabbit eyes and skin.
Chronic Health Effects :not applicable
Medical Conditions Aggravated :not applicable
Other :none found
Routes of Entry :Skin or eye contact. Neither are known to cause irritation
Emergency/First Aid Procedures:EYES - Flush with water for 15 minutes.
SKIN - Wash with soap and water.
INGESTION - Give several glasses of water but do not induce vomiting. If vomiting occurs, give fluids again. Get medical attention. Never give anything by mouth to an unconscious or convulsing person.
INHALATION - Remove to fresh air. Get medical attention if breathing becomes difficult.

Section 5 Physical Hazard Data

Flammable Limits % :UEL:not applicable LEL:not applicable Flash Point: > 400°F
Extinguishing Media :CO2, Water Spray, Dry chemical
Special Fire Procedures :Evacuate unprotected personnel. Avoid exposure to smoke or other combustion products. Firefighters should wear protective clothing and self-contained breathing apparatus.
Unusual Fire/Explosion Hazards:none found
Materials to Avoid :none reasonably foreseeable.
Hazardous Decomposition Products:CO2, CO, various hydrocarbons and organic silicones
Hazardous Polymerization :will not occur Conditions to Avoid:not applicable
Stability :stable Conditions to Avoid:not applicable

Section 6 Spill or Leak Procedures

Accidental Spill Procedures : Absorb spill with sand or Fuller's earth. Sweep up and place in appropriate chemical waste containers. Flush area with water. Clean thoroughly as residue is slippery.

Waste Disposal Method : Observe all local, state, and federal regulations regarding disposal and cleanup

Section 7 Exposure Control Information

Respiratory Protection : NIOSH approved organic vapor mask with prefilters in absence of local exhaust
Ventilation Local Exhaust: preferred Mechanical : recommended
Protective Equipment -- Gloves: chemical resistant Eyes : safety glasses
Other Protective Equipment : Eye wash and personal hygiene facilities should be available in work area.
Work Practices : Employ good industrial housekeeping and personal hygiene. Eating, smoking, and drinking should be avoided in areas where material is in use.
Hygienic Practices : Wash thoroughly after use before eating, drinking and smoking.

Section 8 Special Precautions

Handling and Storing : Minimize air exposure to prolong shelf life. Store in a cool, dry, well ventilated area. Exercise due caution to prevent damage to the container.
KEEP OUT OF REACH OF CHILDREN.

Maintenance Personnel : No information

Other : No information

Important Notice

This information has been compiled from sources believed to be timely, accurate and reliable. It is provided in good faith without charge. Because of the inherent nature of the information and products, and because we cannot anticipate or control the many different conditions under which they may be used, Flex Proof Incorporated does not guarantee the applicability or accuracy of this information or the suitability of our products in any individual situation. It is strictly the users responsibility to determine same for each and any use, and therefore, these products are for industrial or professional use only by literate trained adults. They are not to be sold to, nor are they to be used by, the general public under any circumstance whatsoever.

For the same reasons, the products are sold without warranty of any kind whatever, express or implied, including warranties as to merchantability or fitness for a particular use. In any case, our responsibility for claims arising from breach of warranty, negligence or otherwise, is limited to the product purchase price.