

BOWMAN DISTRIBUTION MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME Maxi-Blue "Easy" Gasket Maker		BOWMAN PART NO. 21498
SUPPLIER BOWMAN DISTRIBUTION, BARNES GROUP INC.		EMERGENCY TELEPHONE NO.: (216) 391-7200
ADDRESS 850 East 72nd Street, Cleveland, OH 44103		DATE 5/7/86
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) Consumer Commodity, ORM-D, UN 1956		
ADDITIONAL HAZARD CLASSES (as applicable) None		
CHEMICAL FAMILY	FORMULA TM-BP116	

SECTION II - HAZARDOUS INGREDIENTS

CAS REGISTRY NO.	%W	%V	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
unknown			Methyl Tris (Methyl Ethyl Ketoximo) — Silane	None
unknown			Methyl Ethyl Ketoxime (by-product of curing reaction)	None
unknown			Organotin Catalyst	None
			Not believed to be hazardous; included for medical information only.	

SECTION III - PHYSICAL DATA

BOILING POINT _____ °F _____ °C N.A.	SPECIFIC GRAVITY (H₂O = 1)	1.0-1.4	
VAPOR PRESSURE 70 mm Hg <input checked="" type="checkbox"/> psi @ _____ °F _____ °C	PERCENT VOLATILE BY VOLUME (%)	N.A.	PERCENT SOLID BY WEIGHT (%) 100%
VAPOR DENSITY (AIR = 1) 4.0	EVAPORATION RATE (= 1)	N.A.	
SOLUBILITY IN WATER none	pH =	None	
APPEARANCE AND ODOR Plaste like slight medicinal odor			MATERIAL IS: PASTE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT >200 °F _____ °C method used TCC	FLAMMABLE LIMITS	LEL none	UEL none
EXTINGUISHING MEDIA Use waterfog, dry chemical or carbon dioxide			
SPECIAL FIRE FIGHTING PROCEDURES May rupture when heated. Contents under pressure; wear self-contained breathing apparatus.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Heated cans may burst. During fire toxic gases such as CO and Oxide of Silicon may be present.			

35

EFFECTS OF OVEREXPOSURE - Conditions to avoid Vapors Irritating to eyes and respiratory tract. Direct contact irritating to skin and eyes.	THRESHOLD LIMIT VALUE PERMISSIBLE EXPOSURE LIMIT None OTHER LIMIT (while curing) 10PPM
PRIMARY ROUTES OF ENTRY Inhalation <input type="checkbox"/> Skin Contact <input type="checkbox"/> Other (specify) _____ Not established	
EMERGENCY AND FIRST AID PROCEDURES Give oxygen — Do not induce vomiting — Gastric lavage — wash eyes and skin with water.	

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Humid condition — product cures on exposure to humidity.
INCOMPATIBILITY (materials to avoid) None			
HAZARDOUS DECOMPOSITION PRODUCTS: Not established			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	None

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Use absorbent sweeping compound to soak up material. Put into container and dispose as hazardous waste.	
WASTE DISPOSAL METHOD Dispose in normal landfill as synthetic rubber.	
RCRA (Superfund) REPORTABLE QUANTITY (in lbs) None	
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) Not a hazardous waste	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water) None	
<input type="checkbox"/> Theoretical _____ lb/gal	<input type="checkbox"/> Analytical _____ lb/gal

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type) Self contained breathing apparatus if above TLV limit.		
VENTILATION	LOCAL EXHAUST (specify rate) yes	SPECIAL none
	MECHANICAL (general) (specify rate) none	OTHER none
PROTECTIVE GLOVES (specify type) none required if spraying		EYE PROTECTION (specify type) wear eye protection
OTHER PROTECTIVE EQUIPMENT long sleeves and long pants		

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Keep away from heat, sparks or open flame. Store at temperatures below 120° F.	
OTHER PRECAUTIONS None	

21498