



MATERIAL SAFETY DATA SHEET

MSDS No. 11156000
ENGLISH

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: AMOCO PREMIER DIESEL FUEL

MANUFACTURER/SUPPLIER:
Amoco Oil Company
200 East Randolph Drive
Chicago, Illinois 60601 U.S.A.

EMERGENCY HEALTH INFORMATION:
1 (800) 447-8735

EMERGENCY SPILL INFORMATION:
1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT SAFETY INFORMATION:
(312) 856-3907

2.0 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u>	<u>CAS#</u>	<u>Range % by Wt.</u>
Petroleum distillate	68334-30-5	95-100
Naphthalene	91-20-3	0-1
Xylene	1330-20-7	0-1

(See Section 8.0, "Exposure Controls/Personal Protection", for exposure guidelines)

3.0 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Warning! Combustible. Harmful or fatal if liquid is aspirated into lungs. Causes skin irritation on prolonged or repeated contact.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: No significant health hazards identified.

SKIN CONTACT: Causes skin irritation on prolonged or repeated contact. See "Toxicological Information" section (Section 11.0).

INHALATION: No significant health hazards identified for the liquid fuel. See "Toxicological Information" section (Section 11.0).

INGESTION: Harmful or fatal if liquid is aspirated into lungs. See "Toxicological Information" section (Section 11.0).

HMIS CODE: (Health:2) (Flammability:2) (Reactivity:0)

NFPA CODE: (Health:2) (Flammability:2) (Reactivity:0)

4.0 FIRST AID MEASURES

EYE: Flush eyes with plenty of water.

SKIN: Wash exposed skin with soap and water. Remove contaminated clothing, including shoes, and thoroughly clean and dry before reuse.

INHALATION: If adverse effects occur, remove to uncontaminated area.

INGESTION: If swallowed, do NOT induce vomiting. Get immediate medical attention.

5.0 FIRE FIGHTING MEASURES

FLASHPOINT: 120-180°F (Tag closed cup)

UEL: 7.5%

LEL: 0.6%

AUTOIGNITION TEMPERATURE: Not determined.

FLAMMABILITY CLASSIFICATION: Combustible Liquid.

EXTINGUISHING MEDIA: Agents approved for Class B hazards (e.g., dry chemical, carbon dioxide, foam, steam) or water fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid.

FIRE-FIGHTING EQUIPMENT: Firefighters should wear full bunker gear, including a positive pressure self-contained breathing apparatus.

PRECAUTIONS: Keep away from sources of ignition (e.g., heat and open flames). Use with adequate ventilation.

HAZARDOUS COMBUSTION PRODUCTS: Incomplete burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

6.0 ACCIDENTAL RELEASE MEASURES

Remove or shut off all sources of ignition. Prevent spreading by diking, ditching, or absorbing on inert materials. Keep out of sewers and waterways.

7.0 HANDLING AND STORAGE

HANDLING: Use with adequate ventilation. Keep away from ignition sources (e.g., heat, sparks, or open flames). Ground and bond containers when transferring materials. Wash thoroughly after handling.

STORAGE: Store in combustible liquids storage area. Store away from heat, ignition sources, and open flame in accordance with applicable regulations.

8.0 EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE: None required; however, use of eye protection is good industrial practice.

SKIN: Avoid prolonged or repeated skin contact. Wear protective gloves if prolonged or repeated contact is likely.

INHALATION: Use with adequate ventilation.

ENGINEERING CONTROLS: Control airborne concentrations below the exposure guidelines.

EXPOSURE GUIDELINES:

<u>Component</u>	<u>CAS#</u>	<u>Exposure Limits</u>
Petroleum distillate	68334-30-5	No exposure limit established
Naphthalene	91-20-3	OSHA PEL: 10 ppm (1989)(1971) OSHA STEL: 15 ppm (1989); Not established. (1971) ACGIH TLV-TWA: 10 ppm ACGIH TLV-STEL: 15 ppm
Xylene	1330-20-7	OSHA PEL: 100 ppm (1989)(1971) OSHA STEL: 150 ppm (1989); Not established. (1971) ACGIH TLV-TWA: 100 ppm ACGIH TLV-STEL: 150 ppm

9.0 CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE AND ODOR: Liquid. Clear or red. Petroleum odor.

pH: Not determined.

VAPOR PRESSURE: Not determined.

VAPOR DENSITY: Not determined.

BOILING POINT: 340-675°F (approximate range)

MELTING POINT: Not determined.

SOLUBILITY IN WATER: Negligible, below 0.1%.

SPECIFIC GRAVITY (WATER = 1): 0.85 to 0.88

VISCOSITY: 1.8-3.6cSt at 100°F

10.0 STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Keep away from ignition sources (e.g. heat, sparks, and open flames).

MATERIALS TO AVOID: Avoid chlorine, fluorine, and other strong oxidizers.

HAZARDOUS DECOMPOSITION: None identified.

HAZARDOUS POLYMERIZATION: Will not occur.

11.0 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY DATA:

EYE IRRITATION: Similar products have produced maximum eye irritation scores ranging from 0.33 to 1.0/110.0; 24 hours (rabbits).

SKIN IRRITATION: Similar products have produced primary skin irritation scores ranging from 0.67 to 3.83/8.0 (rabbits). Dermal LD50 for similar products was greater than 2g/kg; practically non-toxic for acute exposures by this route.

DERMAL LD50: Testing not conducted. See Other Toxicity Data.

ORAL LD50: For a similar product oral LD50 was greater than 5g/kg; practically non-toxic for acute exposures by this route.

INHALATION LC50: Testing not conducted. See Other Toxicity Data.

OTHER TOXICITY DATA:

Middle distillate: From skin-painting studies of petroleum distillates of similar composition and distillate range, it has been shown that these types of materials often possess weak carcinogenic activity in laboratory animals. In these tests, the material is painted on the shaved backs of mice twice a week for their lifetime. The material is not washed off between applications. Therefore, there may be a potential risk of skin cancer from prolonged or repeated skin contact with this product in the absence of good personal hygiene. This particular product has not been tested for carcinogenic activity, but we have chosen to be cautious in light of the findings with other distillate streams.

Occasional skin contact with this product is not expected to have serious effects, but good personal hygiene should be practiced and repeated skin contact avoided. This product can also be expected to produce skin irritation upon prolonged or repeated skin contact. Personal hygiene measures taken to prevent skin irritation are expected to be adequate to prevent risk of skin cancer.

Materials of this type have been shown to produce kidney damage in male rats following prolonged inhalation exposures. Following extensive research, this effect appears to be unique to the male rat and is considered to be of little or no relevance in terms of human health risk.

This product has a sufficiently low vapor pressure to prevent a hazardous buildup of vapors unless the product is heated, used in a confined space with inadequate ventilation or misted. Inhalation of mist or high concentrations of vapors can produce dizziness, headache, and nausea and possibly irritation of the eye, nose and throat.

Aspiration of this product into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Do not siphon by mouth.

NIOSH has recommended that whole diesel exhaust be regarded as a potential occupational carcinogen, based on findings of carcinogenic responses in laboratory animals exposed to whole diesel exhaust. The excess cancer risk for workers exposed to diesel exhaust has not been calculated; however, exposure should be minimized to reduce potential risk.

No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

12.0 ECOLOGICAL INFORMATION

Ecological testing has not been conducted on this product.

13.0 DISPOSAL INFORMATION

Disposal must be in accordance with applicable federal, state, or local regulations. Enclosed-controlled incineration is recommended unless directed otherwise by applicable ordinances.

The container for this product can present explosion or fire hazards, even when emptied! To avoid risk of injury, do not cut, puncture, or weld on or near this container. Since the emptied containers retain product residue, follow label warnings even after container is emptied.

14.0 TRANSPORTATION INFORMATION

U.S. DEPT OF TRANSPORTATION

Shipping Name	:	Diesel Fuel
Hazard Class	:	Combustible liquid.
Identification Number	:	NA1993
Packing Group	:	III

INTERNATIONAL INFORMATION:

Sea (IMO/IMDG)

Shipping Name	:	Not determined.
---------------	---	-----------------

Air (ICAO/IATA)

Shipping Name	:	Not determined.
---------------	---	-----------------

European Road/Rail (ADR/RID)

Shipping Name	:	Not determined.
---------------	---	-----------------

Canadian Transportation of Dangerous Goods

Shipping Name	:	Not determined.
---------------	---	-----------------

15.0 REGULATORY INFORMATION

CERCLA SECTIONS 102A/103 HAZARDOUS SUBSTANCES (40 CFR PART 302.4): This product is exempt from the CERCLA reporting requirements under 40 CFR Part 302.4. However, if spilled into waters of the United States, it may be reportable under 33 CFR Part 153 if it produces a sheen.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR PART 355): This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA TITLE III SECTIONS 311/312 HAZARDOUS CATEGORIZATION (40 CFR PART 370): This product is defined as hazardous by OSHA under 29 CFR Part 1910.1200(d).

SARA TITLE III SECTION 313 (40 CFR PART 372): This product contains the following substance(s), which is on the Toxic Chemicals List in 40 CFR Part 372:

Component/CAS Number	Weight Percent
Xylene 1330-20-7	1
Naphthalene 91-20-3	1

U.S. INVENTORY (TSCA): Listed on inventory.

OSHA HAZARD COMMUNICATION STANDARD: Combustible liquid. Irritant.

EC INVENTORY (EINECS/ELINCS): Not determined.

JAPAN INVENTORY (MITI): Not determined.

AUSTRALIA INVENTORY (AICS): Not determined.


KOREA INVENTORY (ECL): Not determined.

CANADA INVENTORY (DSL): Not determined.

PHILIPPINE INVENTORY (PICCS): Not determined.

16.0 OTHER INFORMATION

BY:



Donald M. Barker, Director
Product Stewardship & Toxicology

Issued: January 05, 1995
Supersedes: April 08, 1994

This material Safety Data Sheet conforms to the requirements of ANSI Z400.1.

This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in this data sheet which we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either express or implied.